



KOPOS

NO MORE QUESTIONS,
WHICH ONE TO CHOOSE!

NEW BRACKET MEDIUM DS

- Unified look for different types of use
- Magnelis® finish is suitable for installations for indoor and outdoor applications
- Same bracket design in stainless steel
- Bracket width of 40 mm allows wall mounting and ceiling or mounting profiles
- Bracket perforations allow for the attachment of cable trays, cable ladders and wire trays
- Medium mechanical load
- One anchor point

www.kopos.com



ASSORTMENT OVERVIEW

MAGNELIS®

new bracket - medium	A (mm)	B (mm)	max. load (kg)	original brackets			
DS 62_ZM	82	44	150	NPS 62_ZNCR	NPS 62_F		
DS 100_ZM	120	49	150	DS 100_S	DSN 100_S	DSN 100_F	DLN 100_S
DS 125_ZM	145	49	150	NPS 125_ZNCR	NPS 125_F		
DS 150_ZM	170	60	150	DS 150_S			DLN 150_S
DS 200_ZM	220	64	150	DS 200_S	DSN 200_S	DSN 200_F	DLN 200_S
DS 250_ZM	270	64	150	NPS 250_ZNCR	NPS 250_F		
DS 300_ZM	320	74	130	DS 300_S	DSN 300_S	DSN 300_F	DLN 300_S
DS 400_ZM	420	84	130	DS 400_S	DSN 400_S	DSN 400_F	
DS 500_ZM	520	94	130	DS 500_S	DSN 500_S		
DS 600_ZM	620	119	130	DS 600_S	DSN 600_S		

STAINLESS STEEL

new bracket - medium	A (mm)	B (mm)	max. load (kg)	original brackets			
INOXDS 62_IX	82	44	150	NIXDS 62_IX			
INOXDS 100_IX	120	49	150		INOXDZDS 100/B_BX		
INOXDS 125_IX	145	49	150	NIXDS 125_IX			
INOXDS 150_IX	170	60	150		INOXDZDS 150/B_BX		
INOXDS 200_IX	220	64	150	INOXDS 200_IX	INOXDZDS 200/B_BX		
INOXDS 250_IX	270	64	150	NIXDS 250_IX			
INOXDS 300_IX	320	74	130	INOXDS 300_IX	INOXDZDS 300/B_BX		
INOXDS 400_IX	420	84	130	INOXDS 400_IX	INOXDZDS 400/B_BX		
INOXDS 500_IX	520	94	130	NIXDS 500_IX			

